

Aluminum Rolling Ladder



Standard Features

- 57 degree industrial slope
- 18" or 24" wide steps
- Tilt & Roll design on 5" rigid casters
- Non-marring rubber tips at stabilizing legs
- 14" deep top platform
- 300 lbs load rating
- 1" square aluminum construction
- 30" handrails if equipped
- Cleaned mill finish

Optional Items Available

- 500 lbs load rating HEAVY DUTY
 - Different caster design
 - Deeper top platform
 - Top walk-off access with chain or gate
 - California OSHA compliant design
- See "Optional Items" page for more

Item #	Steps	Platform Height	Platform Width	Overall Height	Base W x D	Weight
BA2S18	2	20"	18"	20"	20"x18"	16 lbs
BA2S30	2	20"	24"	20"	26"x18"	22 lbs
BA2SH18	2	20"	18"	50"	20"x18"	20 lbs
BA2SH30	2	20"	24"	50"	26"x18"	25 lbs
BA3S18	3	30"	18"	30"	20"x25"	22 lbs
BA3S30	3	30"	24"	30"	26"x25"	29 lbs
BA3SH18	3	30"	18"	60"	20"x25"	25 lbs
BA3SH30	3	30"	24"	60"	26"x25"	32 lbs
BA4S18	4	40"	18"	40"	20"x31"	27 lbs
BA4S30	4	40"	24"	40"	26"x31"	35 lbs
BA4SH18	4	40"	18"	70"	20"x31"	31 lbs
BA4SH30	4	40"	24"	70"	26"x31"	40 lbs
BA5SH18	5	50"	18"	80"	22"x39"	41 lbs
BA5SH30	5	50"	24"	80"	30"x30"	52 lbs
BA6SH18	6	60"	18"	90"	22"x46"	47 lbs
BA6SH30	6	60"	24"	90"	30"x46"	59 lbs
BA7SH18	7	70"	18"	100"	22"x53"	52 lbs
BA7SH30	7	70"	24"	100"	30"x53"	66 lbs
BA8SH30	8	80"	24"	110"	32"x61"	76 lbs
BA9SH30	9	90"	24"	120"	32"x67"	86 lbs
BA10SH30	10	100"	24"	130"	32"x74"	98 lbs